

Housing Devices, Inc.

ADA 120[®] Audio Visual Alert System

(For the Hearing & Visually Impaired)

STANDARD FEATURES:

- Vandal Proof 16 gauge Stainless Steel Construction
- Dual Audio & Visual Alarms for the Hearing & Visual Impaired
- Adjustable Timer (Alarm)
- Push Button Rest Switch
- Toggle On-Off Switch and SuperBrite[®] LED Power Indicator
- Flashing Strobe Light (110 Candela)
- High Volume (90dbA) Piezoelectric alarm
- 12-14 VDC Wall Mounted Plug-In Transformer or 24VAC Hardwired
- Surface (Std.) or Flush Mounted Unit
- Remote Units available for Multiple Location installations
- Custom Designed Systems available
- Optional Polished or Brushed Brass Finish
- Optional Braille Instructional Signs

DESCRIPTION:

The ADA 120[®] is a modular device which enables people with visual and/or hearing impairments to be made aware of incoming telephone calls and/or when visitors to their residence are outside their front door and ringing the doorbell.

Resident awareness is stimulated via a very loud piezoelectric buzzer and a flashing strobe light. The length of the sound emitted and the strobe flashing may be adjusted from 1-60 seconds and can be RESET anytime in between.

The ADA 120[®] is designed to work with existing residential or building access control systems including: door bell, intercom, telephone entry, and emergency call systems; as well as the standard telephone system (POTS).



ADA 120

6 1/2" x 6 1/2" x 1 3/4"

SYSTEM OPERATION:

Pushing the toggle switch to the "ON" position and then depressing the "RESET" button turns on the unit. When activated the unit will sound a 90dbA piezoelectric buzzer and illuminate a 110 candela flashing strobe light.

Activation is accomplished by pushing the residence's doorbell, or depressing the appropriate residence intercom button, or entering the correct unit number when using a telephone entry system, or by dialing the residence telephone number from a standard telephone system.

Each time the residence is contacted the ADA 120's buzzer will sound and the flashing strobe light will illuminate, notifying the unit's resident that someone is trying to contact them. Depressing the "RESET" button on the unit resets the ADA 120. Up to 5 ADA 120[®] remote units may be used together in a single system.

MOUNTING SYSTEMS & DIMENSIONS

Specify either surface (standard) or flush mounting (consult Mfg.). Flush mounting is accomplished using a back box, surface mounting uses factory supplied brackets.